
TECHNICAL SPECIFICATIONS

The MetaArchive Cooperative



2012-01-20

This document provides an overview of the current recommendations and requirements for administering a preservation cache for the MetaArchive Cooperative, including staffing and hardware. This document was last revised on January 20, 2012.

1. Skills Recommendations

Our Member institutions have identified three key roles that they assign to their local staff members in order to effectively run their caches and prepare their content for ingest into the MetaArchive Preservation Network: cache administration, plugin development, and data wrangling. It is possible that a single technical staff member may be responsible for one or more of these roles. For example, the staff member assigned to plugin development and data wrangling may be the same person (if not they should, if possible, work closely together). The MetaArchive staff regularly provides training for these roles. The anticipated time commitments, skill-sets, and common tasks, as based on current Member experiences, are documented below.

1.1 Cache Administration

Time required	Between 2-10 hrs/mo (average 5 hrs/mo)
Required skills	Basic level administration of UNIX-based platforms; ability to run and maintain servers, proxy servers, firewalls, and RAID configurations
Helpful skills	Knowledge or experience in digital libraries or library IT
Common tasks	Installing a MetaArchive-LOCKSS cache; assisting with content ingest; performing updates for the cache; monitoring the cache; documenting procedures

1.2 Plugin Development for Content Ingest

Time required	Between 2-25 hrs on 1 st plugin (average 15 hrs) Between 1-6 hrs on additional plugins (average 3 hrs)
Required skills	Familiarity with XML; familiarity with file structuring on widely used platforms (Windows/Unix/Linux); understanding of regular expressions; solid understanding of web technologies (e.g., browsers and plugins)
Helpful skills	Familiarity with metadata standards; programming experience; VMWare
Common tasks	Writing/testing plugins

1.3 Data Wrangling

Time required	Between 15-40 hrs per collection (depends on existing repository solution)
Required skills	Familiarity with file structuring on widely used platforms (Windows/Unix/Linux); basic understanding of web technologies (e.g., web servers)
Helpful skills	Experience with re-formatting digital content and media; experience with archival appraisal and selection methods; familiarity with metadata standards and cataloging; programming experience; database management
Common tasks	Creating manifest pages; re-naming and re-sizing files; preparing web servers to deliver content; creating collection level metadata

2. Operational Requirements

2.1. Preparing the Technical Environment

- Member system administrators (or designated technical staff members) should have ready access and authorizations to access their MetaArchive-LOCKSS caches to the fullest extent possible.
- Member system administrators (or designated technical staff members) should have the ability to effectively coordinate with staff members that are responsible for configuring institutional firewalls to allow MetaArchive-LOCKSS caches to participate in the MetaArchive Preservation Network.

2.2. Necessary Cost Expenditures

- Designated Members must purchase hardware that meets the specifications below to operate a MetaArchive-LOCKSS cache.
- Member institutions must be prepared to adequately staff the necessary roles (see Skills Recommendations above) to implement and maintain a MetaArchive-LOCKSS cache throughout the period of their membership.

3. Support and Equipment Life Cycles

3.1. Member Obligations

- Members agree to purchase and maintain the necessary technical hardware (as described below) required to operate a MetaArchive-LOCKSS cache throughout their membership period.
- Members also agree to update their technical hardware on a three-year cycle using the current MetaArchive-LOCKSS cache specifications. This ensures that all of the MetaArchive Preservation Network's equipment is replaced in a manner consistent with industry best practices. This rolling cycle also enables the Cooperative to avoid network-wide uniformity of technical hardware.
- Members also agree to repurpose their technical hardware for the MetaArchive test network when it has reached its three-year end-of-life cycle so long as it is still functioning. Caches re-purposed for the MetaArchive test network will not be subjected to any recovery actions in the event of disk failures. If a member has retired more than one cache, only its most recently retired cache should be part of the test network; older caches may be repurposed as needed by the member for other functions.

3.2. Replacement Option

- In the case of catastrophic circumstances, Members have the ability to request technical and financial assistance with the restoration of a preservation site's caches, software, and collections by the MetaArchive Cooperative. These requests will be reviewed and, at the discretion of the Steering Committee, either approved or denied.

4. Technical Specifications

Required	Recommended	Notes
Machine architecture capable of running an operating system with a Sun or Sun-compatible JVM	Intel Core i7 processor and Intel Core i7 Extreme Edition compatible	(Quad Core Processors based on this architecture is the current standard for new LOCKSS caches)
	Rack-mountable server chassis	Not a hard requirement, but standard for most PLNs.
At least 6 GB of RAM	6 or more GB of RAM	At a lower level, excessive swapping may occur.
16 TB Raw disk space RAID Level 5 storage	16-24 TB Raw Disk failures are not uncommon. Using RAID 5 gives us some protection at minimal cost.	This (16TB) is the space configured on the current generation of servers and the previous generation of servers. 16 TB of raw space should be considered the minimum for a new production cache. RAID 5 sacrifices usable disk space but protects against the failure of a single drive
RPM-based Linux Distribution (The proper OS is installed at the factory by recommended vendors.)	CentOS 5.x	The highly recommended distributions are 1) Red Hat Enterprise Server; 2) CentOS
Java Virtual Machine version 1.6 or later		LOCKSS software requires a Java Virtual Machine; any version starting from 1.6 should run the LOCKSS daemon.
LOCKSS software (The LOCKSS software is installed and tested at the factory when using recommended vendors.)		The Cooperative provides a link to the current version that is in use. All caches run the same version of the LOCKSS daemon and we synchronize any upgrades.
LOCKSS caches should be physically secure, accessible only to appropriate staff members, and climate controlled		Temperature of 40-80°F and humidity of 10-80%.
A firewall should be used to block access to all unused ports		Any services not required for functionality and maintenance of a cache should be protected by a firewall. Appropriate ports to leave open include ports used by: 1) the Meta-Archive Preservation Network, and 2) the administrative servers to communicate with the node itself. For Unix machines, ssh should be considered an appropriate method of remote access. Telnet and VNC are not considered secure methods.
User accounts should be kept to a minimum		Only the system administrators who need to maintain the server should have user accounts. These accounts should have strong passwords.
There should be no direct remote administrative access		In the case of SSH, this constitutes disabling root logins.
Security patches should be applied promptly	Always follow local site security update policies.	For users of RPM-based Linux distributions, this can be achieved by periodically running yum or up2date for software updates. In general this is handled by the creation of a cron job when the server goes through the Kickstart procedure.